

Strapping Product Guide

Venhart No. 1 PP Machine Rolls

Designed for use with strapping machines. Ensure your packages are securely strapped during transit and storage with the Venhart No. 1 Machine Rolls. Made from virgin polypropylene, the Venhart No. 1 Machine Rolls provide an economical solution without compromising on durability and quality.



Product Code	Size	Size Max. Tensile Colour Strength		Rolls per Ctn	Roll Weight	Min. Order
S4145006	6mm x 4000m	50kg	Clear	2 rolls	7.5kg	1 ctn
S4230_12	12mm x 3000m	90kg	Clear, Blue	2 rolls	10.5kg	1 ctn
S4325_15	15mm x 2500m	130kg	Clear, Blue	2 rolls	10.5kg	1 ctn

Colour Key: Blue = 4, Clear = 7

For product code: Underscore = colour number. E.g 15mm blue product code = \$4325415

Venhart No. 2 PP Hand Rolls

Designed for use with hand strapping tools. Made from polypropylene, the Venhart No. 2 Rolls provide an economical solution without compromising on durability and quality. The polypropylene strapping is wound on 140mm inner diameter x 110mm width cores. Also available in a self-dispensing centre-draw box that does not require a dispenser.



Product Code	Size	Max. Tensile Strength	Colour	Rolls per Ctn	Roll Weight	Min. Order
S2210_12	12mm x 1000m	90kg	Blue, Yellow, Clear	5 rolls	3.6kg	1 ctn
S2210_15	15mm x 1000m	112kg	Blue, Yellow	5 rolls	4.4kg	1 ctn
S2210419	19mm x 1000m	135kg	Blue	5 rolls	5.25kg	1 ctn





Boxed Centre Draw 0.5-0.6mm thickness

Product Code	Size	Max. Tensile Strength	Colour	Rolls per Ctn	Roll Weight	Min. Order
S2410_12	12mm x 1000m	90kg	Blue, Yellow, Clear	5 rolls	3.5 - 3.8kg	1 ctn
S2410_15	15mm x 1000m	112kg	Blue, Yellow, Clear	5 rolls	4.5 - 5.6kg	1 ctn
S2410_19	19mm x 1000m	135kg	Blue, Yellow	5 rolls	5.25 - 6.5kg	1 ctn

Venhart Heavy PP Band Rolls

The Venhart Heavy Band Rolls provide extra strength for heavier and bulkier items during transit and storage. Made from polypropylene that is thicker than standard PP strapping. Designed for use with strapping hand tools and battery tools such as the VH97A. The black heavy band strapping is also available in a self-dispensing centre-draw box that requires no dispenser.



Product Code	Size	Thickness	Max. Tensile Strength	Colour	Rolls per Ctn	Roll Weight	Min. Order
S3210012	12mm x 1000m	0.8mm	160kg	Black	2 rolls	6.5 - 7kg	1 ctn
S3221016	15mm x 1000m	0.85mm - 0.9mm	200kg	Black	2 rolls	8.26 - 8.6kg	1 ctn
S3410017	19mm x 1000m	0.85mm - 0.9mm	300kg	Black	2 rolls	11 - 11.4kg	1 ctn
S3225015	15.5mm x 250m	0.8mm	185kg	Silver	8 rolls	2.5kg	1 ctn
S3410019	19mm x 1000m	0.8mm	270kg	Burgundy	2 rolls	9.25 - 11kg	1 ctn
S3406018	19mm x 600m	0.8mm	135kg	Black in self-dispen- sing box	5 rolls	6kg	1 ctn





Polyester (PET) Flat and Embossed Strapping

A high quality polyester strapping, designed for use with hand strapping tools and battery operated tools. Our polyester strapping boasts impressive tensile strength, making it almost as strong as steel strapping, yet six times lighter for easier and safer handling. Available in a flat or embossed finish. All PET strapping is wound on a 406mm inner diameter x 150mm width core.



Product Code	Size	Туре	Colour	Max. Tensile Strength	Rolls per Ctn	Roll Weight	Min. Order
S7113200	13mm x 2000m x 0.62mm	Smooth	Light Green	360kg	1 roll	20.5kg	1 roll
S7113201	13mm x 2000m x 0.62mm	Embossed	Light Green	320kg	1 roll	19.4kg	1 roll
S7116100	16mm x 1000m x 0.9mm	Smooth	Light Green	400kg	1 roll	14.4kg	1 roll
S7119100	19mm x 1000m x 1.0m	Smooth	Light Green	580kg	1 roll	23kg	1 roll

Stainless Steel Strapping

Stainless steel's natural resistance to rust makes Venhart Stainless Steel Strapping suitable for applications which are exposed to the weather. Used throughout various industries such as agriculture, building, food, and warehousing.



Product Code	Size	Thickness	Pack	Min. Order
S5340013	13mm x 30m	0.7mm	5	1 roll
S5340016	16mm x 30m	0.7mm	5	1 roll
S5340020	20mm x 30m	0.7mm	5	1 roll





Steel Strapping

Cold rolled and tempered steel to increase strength of steel strapping. Available in blued colour or painted black to prevent rust. Used throughout various industries such as agriculture, building, transportation, and warehousing.

Blue steeled core: Approx. 152.4mm I.D X 432mm O.D

Black painted tempered steel core: Approx. 203.2mm I.D X 432mm O.D



Product Code	Size	Thickness	Colour	Break load	Pack	Approx. weight per roll	Min. Order
S5101515	15.9mm x 281m	0.5mm	Blued	420 kg	3	15.3-17.5kg	1 pack
S5101619	19mm x 234m	0.6mm	Blued	635 kg	3	18.4-21kg	1 pack
S5105619	19mm x 202-234m	0.6mm	Black	F800 kgf	3	18-21kg	1 pack



