

M1660AW with weighing system



PRODUCT DESCRIPTION

No double handling required with the M1660AW - simply weigh each pallet as it is wrapped. Customise the number of top, middle, and bottom reinforcement wraps within 3 automatic programs. Carriage speed, turntable speed, and film tension can be adjusted even while the wrapping continues.

In manual mode, reinforcement wraps can be applied to any position and the wrapping paused then resumed after adding a top sheet.

Other features include power pre-stretch, automatic film cut off and a one-way roller to prevent the film from springing back after it is cut. A safety stop prevents the film carriage from falling if power is cut.



PRODUCT FEATURES

- Weighing system built in
- Turntable soft start and stop
- Forklift slots for easy re-location
- Turntable automatically returns to home position
- Control panel rotates 180 degrees for user convenience
- Servicing and spare parts available



MACHINE SPECIFICATIONS

Note: The following technical information and data should be considered representative or typical only.

Machine weight	516kg	Film width	500mm
Turntable speed	12rpm	Maximum pallet size	1150mm x 1150mm
Pallet height max	2 metres	Pallet load max	1650kg
Turntable diameter	1650mm	Power supply	240V
Film pre-stretch settings	300% and 230%	Power consumption	1.2kw
Film roll diameter max	250mm		