

TECHNICAL INFORMATION

VH881HC AND VH881HC-30 BAND SEALERS



VH881HC-30



PRODUCT DESCRIPTION

Venus' VH881HC and VH881HC-30 Benchtop Heat Sealers offer a simple and compact packaging line for sealing LDPE, PE, PP, PVC, cello and layered barrier bags. Best for items that need to lie flat such as magazines and stationery.

Bags or pouches are placed on the conveyor and travel through the heating elements which seal the tops of the bag. The conveyor speed and sealing head are both adjustable to suit each individual production run.

Both models come in two directional options: left to right or right to left operation. The preferred operation must be specified at the time of purchase. Both models come with a basic embossing kit. A photo activated thermal imprint printer that can print two lines of 14 characters each is an additional option that can be added to the VH881HC model only.

The VH881HC-30 features an extra wide 300mm conveyor.

/

PRODUCT FEATURES

- Safety guard
- Seal width control
- Conveyor alignment adjustment
- Conveyor height adjustment

- Sealing pressure control
- Minimum assembly required
- Servicing and spare parts available





VH881HC AND VH881HC-30 BAND SEALERS



MACHINE SPECIFICATIONS

Machine Weight VH881HC: 25kg | VH881HC-30: 38kg

Bag Length Sealing head to outer edge of conveyor 150mm

Maximum Seal Speed Up to 12 metres / minute

Seal Width 10mm

Conveyor Table Width VH881HC: 150mm | VH881HC-30: 300mm

Temperature Range 30–300°C

Seal Distance Below Bag Top Adjustable from 0 to 30mm

Belt Loading Capacity 2kg

Maximum Seal Thickness 2 x 0.4mm (PE)

Power Consumption 550w







